

# United States Patent and Trademark Office



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/629,948	07/30/2003 ·	Ulrich Botzel	L&L-10044 8888	
24131 7590 04/20/2007 LERNER GREENBERG STEMER LLP			EXAMINER	
P O BOX 2480			CHAN, SAI MING	
HOLLYWOOI	D, FL 33022-2480	TL 33022-2480 ART UNIT PAPER NUMBER		PAPER NUMBER
			2609	
<b></b>				
SHORTENED STATUTOR	Y PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE	
3 MO	NTHS	04/20/2007	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

<u> </u>		
	Application No.	Applicant(s)
	10/629,948	BOTZEL ET AL.
Office Action Summary	Examiner	Art Unit
	Sai-Ming Chan	2609
The MAILING DATE of this communication ap Period for Reply	pears on the cover sheet with the	correspondence address
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D.  - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period.  - Failure to reply within the set or extended period for reply will, by statut Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATIO 136(a). In no event, however, may a reply be to will apply and will expire SIX (6) MONTHS from the, cause the application to become ABANDONI	N. mely filed n the mailing date of this communication. ED (35 U.S.C. § 133).
Status	•	
1) Responsive to communication(s) filed on 30 J	<i>luly</i> 2003.	
2a) This action is <b>FINAL</b> . 2b) ⊠ Thi	s action is non-final.	
3) Since this application is in condition for allowa	ance except for formal matters, pr	osecution as to the merits is
closed in accordance with the practice under	Ex parte Quayle, 1935 C.D. 11, 4	53 O.G. 213.
Disposition of Claims		
4) ☐ Claim(s) 1-30 is/are pending in the application 4a) Of the above claim(s) is/are withdra 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-30 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/o	awn from consideration.	
Application Papers		
9) ☐ The specification is objected to by the Examine 10) ☑ The drawing(s) filed on 30 July 2003 is/are: a) Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the E	)⊠ accepted or b)⊡ objected to e drawing(s) be held in abeyance. Se ction is required if the drawing(s) is ot	e 37 CFR 1.85(a). Djected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:  1. Certified copies of the priority documen 2. Certified copies of the priority documen 3. Copies of the certified copies of the priority application from the International Burea * See the attached detailed Office action for a list	nts have been received.  Its have been received in Applicatority documents have been received in Rule 17.2(a)).	ion No ed in this National Stage
Attachment(s)	<b></b>	(DTO 110)
<ol> <li>Notice of References Cited (PTO-892)</li> <li>Notice of Draftsperson's Patent Drawing Review (PTO-948)</li> <li>Information Disclosure Statement(s) (PTO/SB/08)</li> <li>Paper No(s)/Mail Date 7/30/2003 and 5/19/2005.</li> </ol>	4)  Interview Summar Paper No(s)/Mail D 5)  Notice of Informal 6)  Other:	Pate

### **DETAILED ACTION**

### **Priority**

Receipt is acknowledged of papers submitted under 35 U.S.C. 119(a)-(d), which papers have been placed of record in the file.

#### Information Disclosure Statement

The information disclosure statements (IDS) submitted on July 30, 2003 and May 19, 2005 have been considered by the Examiner and made of record in the application file.

## Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

- 1. Determining the scope and contents of the prior art.
- 2. Ascertaining the differences between the prior art and the claims at issue.
- 3. Resolving the level of ordinary skill in the pertinent art.
- 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

Claims 1-30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Scott (U.S. Patent # 6388997), in view of Johansson (U.S. Patent # 6975613).

Consider **claim1**, Scott clearly discloses and shows a data transmission system, comprising:

a base station (fig. 3a (304)) and at least two mobile stations (fig. 3a (302) for interchanging data bursts successively by radio (fig. 8 (transmitter and receiver for radio operation); column 6, lines 6-7) using a time slot method (abstract, lines 5-7; fig. 5a (510 & 511));

a transmitter (fig. 8A (807 transmitter); column 6, lines 6-7) of said base station being configured to transmit first data bursts (fig. 5c (571 - basestation burst)) to said mobile stations, at least some of the first data bursts containing at least two data blocks (fig. 5c (574 has 16 mobile messages); column 20, lines 33-67, column 21, lines 7) intended for different ones of said mobile stations, said transmitter being configured to produce identification information only at a start of a transmission of each of the first data bursts (fig. 5c (574 has one preamble (with the header following it) for all the mobile messages);

each of said mobile stations having a transmitter (fig. 9 (907 transmitter); column 6, lines 11-12) configured to transmit a group of second data bursts (fig. 5c (572 -mobile bursts)) containing a data block intended for said base station (fig. 5c (575s); column 21, lines 38-46), said transmitter being configured to produce identification information (fig. 5c (575 has one preamble (with the header following it) (579) per message);

column 21, lines 38-46) at a start of a transmission of the second data bursts (fig. 5c (575); column 21, lines 38-46); and

a device for producing a guard time interval (base station (fig. 8a (811);column 17, lines 1-9); mobile station (fig.9 (911); column 19, lines 7-15) between the data bursts.

However, Scott does not specially disclose a piconetwork for the data transmission.

In the same field of endeavor, Johansson clearly shows a piconetwork (fig. 2;column 2, lines 61-63).

Therefore it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate data transmission system, as taught by Scott, and show data transmission in a piconetwork, as taught by Johansson, in order to show that data can be transmitted efficiently.

Consider **claim 2**, and **as applied to claim 1 above**, Scott, as modified by Johansson, clearly discloses and shows the data transmission system, wherein said base station and each of said mobile stations have a local oscillator (fig. 18 (1821); column 52, lines 54-58).

Consider **claim 3**, and **as applied to claim 2 above**, Scott, as modified by Johansson, clearly discloses and shows the data transmission system, wherein each of said local oscillators is connected to a respective phase locked loop (fig. 18 (perform at each code phase desired); column 52, lines 1-2, column 53, lines 1-11).

Consider **claim 4**, and **as applied to claim 1 above**, Scott, as modified by Johansson, clearly discloses and shows the data transmission system, wherein the first data bursts and groups of the second data bursts are transmitted alternately (fig. 5c (571 and 572); column 4, lines 64-67, column 5, lines 1-21).

Consider claim 5, and as applied to claim 4 above, Scott, as modified by Johansson, clearly discloses and shows the data transmission, wherein at least one of: the first data burst and a subsequent one of the groups of the second data bursts are at different transmission frequencies (column 5, lines 7-10), and one of the groups of the second data bursts and a subsequent one of the first data bursts are at different transmission frequencies (column 5, lines 7-10).

Consider claim 6, and as applied to claim 5 above, Scott, as modified by Johansson, clearly discloses and shows the data transmission system, wherein one of the transmission frequency of the first data burst and the group of the second data

bursts is constant during a transmission (column 5, lines 7-10 (frequency band is constant for data bursts).

Consider **claim 7**, and **as applied to claim 1 above**, Scott, as modified by Johansson, clearly discloses and shows the data transmission system, wherein the guard time interval between one of the first data bursts and a subsequent one of the second data bursts is equal to the guard time interval between the one of the second data bursts and the subsequent one of the first data bursts (column 4, lines 37-47 (a single collective guard time)).

Consider **claim 8**, and **as applied to claim 1 above**, Scott, as modified by Johansson, clearly discloses and shows the data transmission system, wherein the guard time intervals between successive second data bursts have equal lengths (fig. 5 (573); column 21, lines 38-46).

Consider claim 9, and as applied to claim 1 above, Scott, as modified by Johansson, clearly discloses and shows the data transmission system, wherein:

the first data bursts contain at least two data blocks, with one data block being provided for each of said mobile stations (fig. 5c (578 has 16 mobile messages); column 20, lines 33-67, column 21, lines 7), and

a second data burst from each of said mobile stations is in each case provided in the group of the second data bursts (fig. 5c (each mobile burst in 572 is represented by 575); column 21, lines 38-46)).

Consider claim 10, and as applied to claim 1 above, Scott, as modified by Johansson, clearly discloses and shows the data transmission system, wherein said data transmission system can be used in a system with real-time requirements selected from the group consisting of a cordless communication system, and a computercontrolled entertainment system, a computer-controlled game system (column 49, lines 23-24, lines 31-35).

Consider claim11, Scott clearly discloses and shows a frame structure for radio transmission of data bursts between a base station and at least two mobile stations, comprising:

first data bursts transmitted from the base station to the mobile stations, with at least some of said first data burst (fig. 5c (571 - basestation burst)) containing at least two data blocks, each of said data blocks being intended for different mobile stations ((fig. 5c (574 has 16 mobile messages); column 20, lines 33-67, column 21, lines 7)), and further containing identification information at a start of each of said first data bursts(fig. 5c (574 has one preamble (with the header following it) for all the mobile messages);

Page 9

second data bursts (fig. 5c (572 -mobile bursts)) transmitted from a respective one of the mobile stations to the base station (fig. 5c (575s); column 21, lines 38-46), each of said second data bursts containing a data block intended for the base station and containing identification information at a start of each of the second data bursts(fig. 5c (575 has one preamble (with the header following it) (579) per message); and guard time intervals (base station (fig. 8a (811); column 17, lines 1-9); mobile station (fig.9 (911); column 19, lines 7-15) between successive data bursts.

However, Scott does not specially disclose a piconetwork for the data transmission.

In the same field of endeavor, Johansson clearly shows a piconetwork (fig. 2;column 2, lines 61-63).

Therefore it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate data transmission system, as taught by Scott, and show data transmission in a piconetwork, as taught by Johansson, in order to show that data can be transmitted efficiently.

Consider **claim 12**, and **as applied to claim 11 above**, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein said base station and each of said mobile stations have a local oscillator (fig. 18 (1821); column 52, lines 54-58).

Consider **claim 13**, and **as applied to claim 12 above**, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein each of said local oscillators is connected to a respective phase locked loop (fig. 18 (perform at each code phase desired); column 52, lines 1-2, column 53, lines 1-11).

Consider **claim 14**, and **as applied to claim 12 above**, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein the first data bursts and groups of the second data bursts are transmitted alternately (fig. 5c (571 and 572); column 4, lines 64-67, column 5, lines 1-21).

Consider **claim 15**, and **as applied to claim 14 above**, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein at least one of: the first data burst and a subsequent one of the groups of the second data bursts are at different transmission frequencies (column 5, lines 7-10), and a group of the second data bursts and a subsequent one of the first data bursts are at different transmission frequencies (column 5, lines 7-10).

Consider claim 16, and as applied to claim 15 above, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein one of the

transmission frequency of the first data burst and the group of the second data bursts is constant during a transmission (column 5, lines 7-10 (frequency band is constant for data bursts).

Consider **claim 17**, and **as applied to claim 11 above**, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein the guard time interval between one of the first data bursts and a subsequent one of the second data bursts equals a guard time interval between said second data bursts and subsequent first data bursts (column 4, lines 37-47 (a single collective guard time)).

Consider **claim 18**, and **as applied to claim 11 above**, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein the guard time intervals between successive second data bursts have equal lengths (fig. 5 (573); column 21, lines 38-46).

Consider **claim 19**, and **as applied to claim 11 above**, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein:

the first data bursts contain two data blocks, with one data block being provided for each of said mobile stations (fig. 5c (578 has 16 mobile messages); column 20, lines 33-67, column 21, lines 7), and

said second data burst include a data burst from each of said mobile stations (fig. 5c (each mobile burst in 572 is represented by 575); column 21, lines 38-46)).

Page 12

Consider claim 20, and as applied to claim 11 above, Scott, as modified by Johansson, clearly discloses and shows the frame structure, wherein said data transmission system can be used in a system having a real-time requirements selected from the group consisting of a cordless communication system, and a computer-controlled entertainment system, a computer-controlled game system (column 49, lines 23-24, lines 31-35).

Consider **claim 21**, Scott clearly discloses and shows a method for radio transmission of data between a base station and at least two mobile stations, which comprises the steps:

- (a) transmitting a first data burst from the base station to the mobile stations, the first data burst (fig. 5c (571 basestation burst)) containing at least two data blocks each intended for a different one of the mobile stations (fig. 5c (574 has 16 mobile messages); column 20, lines 33-67, column 21, lines 7), including transmitting identification information only at a start of a transmission of the first data burst (fig. 5c (574 has one preamble (with the header following it) for all the mobile messages);
- (b) providing a guard type interval (base station (fig. 8a (811);column 17, lines 1-9); mobile station (fig.9 (911); column 19, lines 7-15); and

(c) transmitting the second data bursts (fig. 5c (572 -mobile bursts)) from one of the mobile stations to the base station, each of the second data bursts containing a data block intended for the base station (fig. 5c (575s); column 21, lines 38-46), each of the mobile stations transmitting identification information (fig. 5c (575 has one preamble (with the header following it) (579) per message); column 21, lines 38-46) at a start of a transmission of the second data bursts (fig. 5c (575); column 21, lines 38-46).

However, Scott does not specially disclose a piconetwork for the data transmission.

In the same field of endeavor, Johansson clearly shows a piconetwork (fig. 2;column 2, lines 61-63).

Therefore it would have been obvious to a person of ordinary skill in the art at the time the invention was made to incorporate data transmission system, as taught by Scott, and show data transmission in a piconetwork, as taught by Johansson, in order to show that data can be transmitted efficiently.

Consider claim 22, and as applied to claim 21 above, Scott, as modified by Johansson, clearly discloses and shows the method, which further comprises transmitting and receiving data bursts with the base station and each of the mobile stations by using respective local oscillators (fig. 18 (1821); column 52, lines 54-58).

Consider claim 23, and as applied to claim 22 above, Scott, as modified by Johansson, clearly discloses and shows themethod, wherein each of said local oscillators is connected to a respective phase locked loop (fig. 18 (perform at each code phase desired); column 52, lines 1-2, column 53, lines 1-11).

Consider claim 24, and as applied to claim 21 above, Scott, as modified by Johansson, clearly discloses and shows the method, wherein the first data bursts and groups of the second data bursts are transmitted alternately (fig. 5c (571 and 572); column 4, lines 64-67, column 5, lines 1-21).

Consider claim 25, and as applied to claim 23 above, Scott, as modified by Johansson, clearly discloses and shows the method, wherein at least one of: the first data burst and a subsequent group of the second data bursts are at different transmission frequencies (column 5, lines 7-10); and a group of the second data bursts and a subsequent first data burst are at different transmission frequencies(column 5, lines 7-10).

Consider claim 26, and as applied to claim 25 above, Scott, as modified by Johansson, clearly discloses and shows the method, which further comprises keeping

the transmission frequency constant during one of a transmission of the first data burst and a transmission of the group of the second data bursts (column 5, lines 7-10 (frequency band is constant for data bursts).

Page 15

Consider claim 27, and as applied to claim 21 above, Scott, as modified by Johansson, clearly discloses and shows the method, wherein:

the guard time interval is between the first data burst and a subsequent one of the second data bursts (fig. 5a (503) collective guard time)), and

the guard time interval has an equivalent length as between one of the second data bursts and a subsequent first data burst (column 4, lines 37-47 (single collective guard time)).

Consider claim 28, and as applied to claim 21 above, Scott, as modified by Johansson, clearly discloses and shows the method, which further comprises providing guard time intervals of an equivalent length between successive second data bursts (fig. 5 (573); column 21, lines 38-46).

Consider claim 29, and as applied to claim 21 above, Scott, as modified by Johansson, clearly discloses and shows the method, which further comprises:

in the first data bursts, providing at least two data blocks, one of the data blocks being provided for each of the mobile stations (fig. 5c (578 has 16 mobile messages); column 20, lines 33-67, column 21, lines 7); and

providing a second data burst from each of the mobile stations in each of the group of second data bursts (fig. 5c (each mobile burst in 572 is represented by 575); column 21, lines 38-46)).

Consider claim 30, and as applied to claim 21 above, Scott, as modified by Johansson, clearly discloses and shows the method, which further comprises using the method in a system with real-time requirements selected from the group consisting of a cordless communication systems, a computer-controlled entertainment system, and a computer-controlled games system (column 49, lines 23-24, lines 31-35).

#### Conclusion

Any response to this Office Action should be faxed to (571) 273-8300 or mailed

to:

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Hand-delivered responses should be brought to

Customer Service Window Randolph Building 401 Dulany Street Alexandria, VA 22314

Any inquiry concerning this communication or earlier communications from the Examiner should be directed to Sai-Ming Chan whose telephone number is (571) 270-1769. The Examiner can normally be reached on Monday-Thursday from 6:30am to 5:00pm.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's supervisor, Rafael Pérez-Gutiérrez can be reached on (571) 272-7915. The fax phone number for the organization where this application or proceeding is assigned is (571) 273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free) or 571-272-4100.

Application/Control Number: 10/629,948 Page 18

Art Unit: 2609

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist/customer service whose telephone number is (571) 272-2600.

Sai-Ming Chan S.C./ sc

April 11, 2007